



The MegaFlow740-serie is an excellent alternative to bag media but is also ideal for high flow applications. It reduces significantly the number of cartridges necessary for large flow applications. Each MegaFlow cartridge has a 6,5" outside diameter. It can handle flows up to 35m³/hr. Our MegaFlow740 is available in glassfibre and polypropylene. The cartridges are provided with a standard 226 positive o-ring seal and an easy to grip cross handle. All our MegaFlow cartridges do have absolute retention ratings (beta = 5000(99,98% efficiency)). The inside core makes it suitable for the outside to inside flow pattern.

FEATURES

- Absolute rating of Beta 5000 (99.98% efficiency) for reliable results in any critical application.
- Provides significantly higher dirt holding than normal pleated, this means a longer life and use of less elements
- Quick and easy change out with integrated handle .
- Large diameter increases filtration surface area, this means higher flow rates compared to 2,5" filter cartridges
- Full Thermal Bonded technology offering chemical compatibility for most fluids, solvents, chemicals.
- The o-ring seal assures filtration integrity.
- High strength by rigid polypropylene core

APPLICATIONS

- Completion Fluids
- Produced Water
- Workover Fluids
- Gravel Pack Fluids
- Wellbore Cleanup Fluids
- (Bio) diesel
- Surface Water Intake
- Water Injection
- Process Water
- Pre-filtration RO
- Frac Fluids
- Pipeline Flushing
- Waste Water
- Acids
- Solvents

If you need more specifications please sent an email to info@dutchfiltration.com and we sent you the complete datasheet

Contact

Dutch Filtration BV
Vrijheidweg 61
1521 RP, Wormerveer
The Netherlands
+31 (0)75 201 40 00
info@dutchfiltration.com
www.dutchfiltration.com